



MBL450D-4F

COLLICUTT'S LATEST IN POWER GENERATION TECHNOLOGY

MAIN OVERVIEW

This specification outlines the Collicutt MBL450D-4F, trailer mounted, 450kW, Tier 4 Final, prime rated, diesel generator package.



ENGINE

- Scania DC16-084A
- EPA certifiedTier 4f emissions level
- ▶ 450kW prime rating and 495kW standby rating
- ▶ 1800rpm engine speed
- Engine mounted radiator
- ▶ 120V engine coolant heater
- ► 50°C (122°F) cooling system design
- ► 24V control system
- ► Battery charger
- ► ECU override switch for running diagnostic software
- Group 31 batteries
- ▶ 120L (32G) DEF capacity
- Programmable shutdowns
- ► Lockable DEF & fuel fill location
- ▶ Oil level monitoring

ELECTRICAL

- Single motorized main line 1600A main line circuit breaker
- ► Ability to parallel the generator with other units
- Ability to switch between 208V and 480V
- ▶ 400A camlocks for electrical interface
- Deep Sea 8910 controller

ENCLOSURE

- Lockable level 1 enclosure for increased security
- Insulated exhaust tubing inside
- Sound attenuating insulation (75dBA rating at 7m)
- Venting for cooling and engine air consumption
- Rodent/bird guards
- ► Internal 24V lighting system
- ► Removable panels to assist with maintenance
- External emergency stop
- ► Rear DEF and fuel fill
- Customizable paint color and company logo air intake

ALTERNATOR

- Stamford HCI534D
- MX321 voltage regulator
- Capable of 480V @ 625A and 208V @ 1450A
- ► PMG excitation
- ▶ 60Hz
- Dual bearing



GENERATOR DIMENSIONS

► Width: 8' - 5.5"

Length: 26' - 6.5"

► Height: 9' - 10.5"

GENERATOR WEIGHT

23,000lbs or 10,454kg



TRAILER

- ► 620G (2350L) UN31 fuel tank
- ► 12k tandem spring axles
- ► ST235-75-R17.5 wheel assemblies
- Powder coated textured black
- ► 10k drop leg tongue jack
- ► LED lighting
- Removable fenders
- Adjustable 3" pintle eye
- NATM compliant

WARRANTY

- Comprehensive 1-year standard warranty
- 5year/3000hour emissions warranty
- Options to extend warranty

CONSUMPTION

FUEL CONSUMPTION

FULL LOAD 104L/hr (27G/hr)

3/4 LOAD 79L/hr (21G/hr)

1/2 LOAD 55L/hr (14G/hr)

DEF CONSUMPTION

FULL LOAD 4L/hr (1G/hr)



- **©** 888,682,6888
- ♠ info@collicutt.com
- collicutt.com

